

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 62-165944

(43)Date of publication of application : 22.07.1987

(51)Int.Cl.

H01L 21/60

(21)Application number : 61-008407

(71)Applicant : FUJITSU LTD

(22)Date of filing : 17.01.1986


(72)Inventor : MASUYAMA YOSHIHIRO

(54) WIRE CONNECTING METHOD

(57)Abstract:

PURPOSE: To prevent disconnections by applying conductive adhesives to a crushed section by wire bonding and reinforcing the crushed section.

CONSTITUTION: When a small-gage wire 2 consisting of Au, etc. is bonded with a part to be bonded such as a terminal, a joining section is crushed. When conductive adhesives 4 are applied to the joining section and cured, the joining section is reinforced, thus preventing disconnections.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office